



MAGNETIC/STEREO OUTPUT -

WHEN USED WITH A MONO CABLE, THIS OUTPUT PROVIDES A PASSIVE SIGNAL FROM THE MAGNETIC PICKUPS ONLY. WHEN USED WITH A STEREO (TRS) CABLE, TIP OUTPUTS PASSIVE MAGNETIC SIGNAL; RING OUTPUTS BUFFERED PIEZO SIGNAL.

PIEZO/MONO OUTPUT -

USE MONO CABLE ONLY. WHEN ONLY THIS JACK IS CONNECTED, A BUFFERED AND MIXED COMBINATION OF THE MAGNETIC AND PIEZO SIGNALS IS PRODUCED. WHEN BOTH JACKS ARE USED, THIS OUTPUT WILL PRODUCE THE BUFFERED PIEZO SIGNAL ONLY; THE MAGNETIC SIGNAL IS DIVERTED TO THE MAGNETIC/STEREO OUTPUT.

ERNIE BALL / MUSIC MAN			
AXIS SPORT GUITAR PIEZO/HH CONTROL FUNCTION DIAGRAM			
REV	DRAWN BY HFL	APPROVED BY DDG	DATE 7-7-99
SCALE NONE	TOLERANCE	N/A	PART NO.